




MODEL: ILOGIC MS PLUS **WATTS** 1050W
VOLTAGE: 100 - 277V **SKU** IL-L1050MS

TECHNICAL SPECS

Rated Voltage	100 - 277V
Power Consump	1050W ± 5%
Power Supply	Sosen LED Drivers
ePAR - PPF	3483 µmol/s
ePAR Efficacy - Efficacy	3.05 µmol/J
LED Spectrum	Full Spectrum + UV + FR
Min Power Factor - Power Factor	>0.9
THD	<10%
Crest Factor	<10%
BTU	3500
Frequency	60Hz
Dimming	0 - 100% dimming via RS485
Ambient Temperature - Working	0°C - 35°C / 32° - 95°F
Color Temperature	4000K
Color Rendering Index	85
Relative Humidity	<90%
Emitting Cooling	Aluminum heatsink
Light Distribution - Beam Angle	120 Degree
Waterproof Rating	IP65
LED Lifespan (90% of Life)	50000 hours
Daisy Chain	Unlimited with Plus Repeater
Light Source	Samsung LM281 B+ Pro * 3640pcs Honglitrionic SMD3535 660nm * 280pcs Honglitrionic SMD3030 (UV) * 192pcs Honglitrionic SMD2835 (FR) * 192pcs

PHYSICAL SPECIFICATIONS


Height 75mm / 2.9"
Weight - N.W./G.W. 15kg / 17kg | 33lbs / 37.4lbs
Package Size 1130*625*85mm / 44.5*24.6*3.3"




VOLTAGE AND AMPERAGE

Voltage 120V 208V 220V 240V 277V
Amperage 8.75A 5.05A 4.78A 4.38A 3.79A


SPECTRUM




Full Spectrum
100% ON.




Full Spectrum
ON 100% + UV 100%
ON.




Full Spectrum
100% ON + FR 100%
ON.




UV 100% ON.



FR 100% ON.



UV 100% ON +
FR 100% ON.



Full Spectrum
100% ON + UV 100%
ON + FR 100% ON.




This commercial fixture requires a separately purchased Plus Controller to operate.

5 YEAR
WARRANTY



www.iluminarlighting.com 1-877-540-5588 sales@iluminarlighting.com
© Copyright 2026 ILUMINAR Lighting. Subject to change without notice.

PICTURES



Why Growers Choose Us

- Designed for multi-tier racking systems.
- Built to last with no need for replacements, with removable bars and driver, zero down time in your facility.
- The first smart fixture ever designed to prevent hermaphroditism or re-vegging.